

<b>Version</b>	Worktop - 90 cm - Customisable top panel - 800 m <sup>3</sup> /h
<b>Collection</b>	Design

**TECHNICAL FEATURES**

<b>Materials/Finishes</b>	Smoked tempered glass
<b>Materials/Finishes</b>	Aluminium finishing black matt
<b>Materials/Finishes</b>	Customisable upper panel
<b>Features</b>	Up/Down lift system with height adjustment Motor position adjustment system to optimise cabinet space Grease and odour filter basket with liquid collection tray Automatic cut-off timer
<b>Control</b>	Touch control Dialogue system Remote control (optional)
<b>Function</b>	Extracting/Filtering
<b>Lighting</b>	Dynamic Light (2700K - 5600K) Strip LED 7 W - 2700 K / 5600 K
<b>Filters</b>	Metallic grease filter, removable and washable Carbon.Zeo Microtech regenerable filter (optional)
<b>Motor</b>	Brushless Motor
<b>Dimensions</b>	90 cm



Photograph is for information purposes only. May not correspond to the selected version

**CONNECTION AND CONSUMPTION FUNCTIONS**








<b>Maximum consumption</b>	180 W
<b>Voltage/Frequency</b>	220-240V 50-60Hz

**MOTOR**

<b>Motor</b>	Brushless Motor 800 m <sup>3</sup> /h
<b>Maximum capacity</b>	665 m <sup>3</sup> /h I.E.C.61591
<b>Maximum sound level</b>	64 dB (A)re1pW I.E.C. 60704-2-13
<b>Energy class</b>	A++

**WEIGHTS AND VOLUMES**

<b>Gross weight</b>	39 kg
<b>Net weight</b>	31.9 kg
<b>Volume</b>	0.37 m <sup>3</sup>
<b>Packaging dimensions</b>	L 1070 x H 402 x P 870 mm



Cut-out - activation sensor

**Optional accessories**

Code	Description
KACL.1042	Carbon.Zeo Microtech regenerable filter (2x)
105080053	Remote control

**FLOW RATE / PRESSURE**

PF		
S		
M	Worktop - 90 cm - Customisable top panel - 800 m3/h	
AEC	28.10	kWh/a
EEC	A++	
FDE	40.30	
FDEC	A	
LE	0.30	
LEC	G	
GFE	87	
GFEC	B	
Qmin	435	m <sup>3</sup> /h
Qmax	605	m <sup>3</sup> /h
Qboost	665	m <sup>3</sup> /h
SPEmin	56	dBa
SPEmax	64	dBa
SPEboost	65	dBa
PO		
PS	0.00	W
PI		
F	0.00	
EEl	33.00	
Qbep	414	m <sup>3</sup> /h
Pbep	413	Pa
Qboost	665	m <sup>3</sup> /h
Wbep	119	W
WL	9.00	W
Emiddle	3	lux
Lwa-SPEmax	64	dBa

PF\_Scheda prodotto conforme a 65/2014 S\_Supplier name / M\_Model identification / AEC\_Annual Energy Consumption (AEC hood) / EEC\_Energy Efficiency class / FDE\_Fluid Dynamic Efficiency (FDE hood) / FDEC\_Fluid Dynamic Efficiency class / LE\_Lighting Efficiency (LE hood) / LEC\_Lighting Efficiency class / GFE\_Grease Filtering Efficiency / GFEC\_Grease Filtering Efficiency class / Qmin\_Air flow (in m<sup>3</sup>/h) at min speed in normal use / Qmax\_Air flow (in m<sup>3</sup>/h) at max speed in normal use / Qboost\_Air flow (in m<sup>3</sup>/h) at intensive or boost setting (max air-flow) / SPEmin\_Airborne acoustical A-weighted sound power emissions (in dB) at min speed in normal use / SPEmax\_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost\_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0\_Power consumption in off mode (Po) / Ps\_Power consumption in stand by mode (Ps).

PI\_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F\_Time increase factor / EEL\_Energy Efficiency Index / Qbep\_Measured air flow rate at best efficiency point / Pbep\_Measured air pressure at best efficiency point / Qboost\_Maximum air flow / Wbep\_Measured electric power input at best efficiency point / WL\_Nominal power of the lighting system / Emiddle\_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax\_Sound pressure level at the highest speed.